

Amendments to the claims:

1. (currently amended) A hand-held jigsaw machine with a machine housing (11), a saw blade (13) that is drivable in a reciprocating motion by a motor and that includes a sawtooth strip (131) and a saw blade back (132) diametrically opposed thereto, with a support device (20) with a support roller (23) that supports the saw blade on its back (132), a holder (22) that is fixed to the housing (11) and accommodates the support roller (23) between two arms (222, 223), and a guide device (21) for guiding and supporting the saw blade (13) transversely to the saw direction and that includes guide elements (24, 25) located on opposite sides of the saw blade (13) at an adjustable distance from each other,

wherein the guide device (21) is integrated in the holder (22) of the support device (20), wherein the guide elements (24, 25) are designed as guide disks (26, 27) that have an outer diameter that is greater than the outer diameter of the support roller (23) and enclose the support roller (23) between them, wherein the guide device (21) includes a displacement member (28) for axially displacing the guide disks (26, 27), and wherein the displacement member (28) is coupled with a manual actuating member (29), wherein the displacement member (28) has two identical displacement disks (30, 31), the axial width of which varies across the circumference, wherein one displacement disk (30, 31) each is located between a guide disk (26, 27) and an arm (222, 223) of the holder (22), and wherein a compression spring (37) is located in the interior of support roller (23)

that bears against the two guide disks (26, 27) and presses against the displacement disks (30, 31).

2. (canceled)

3. (currently amended) The hand-held jigsaw as recited in Claim 1 2, wherein one of the guide disks (26) is designed integral with the support roller (23) and the other guide disk (27) is located such that it is axially displaceable on the support roller (23).

4. (canceled)

5. (canceled)

6. (currently amended) The jigsaw machine as recited in Claim 1 5, wherein the support roller (23) and the guide disks (26, 27) are mounted on a shaft (32) that is rotatably accommodated in the arms (222, 223) of holder (22), and wherein the displacement disks (30, 31) and the actuating member (29) are rotatably located on the shaft (32).

7. (currently amended) The hand-held jigsaw machine as recited in Claim 1 [[4]], wherein the actuating member (29) is designed as rotary knob (33).

8. (previously presented) The hand-held jigsaw machine as recited in Claim 6, wherein the guide device (21) includes a locking member (38) for fixing the shaft (32) in its particular rotary position.